

Europäisches Patentamt
European Patent Office
Office européen des brevets



(11) **EP 0 957 665 A2**

(12) **EUROPEAN PATENT APPLICATION**

(43) Date of publication:
17.11.1999 Bulletin 1999/46

(51) Int Cl.⁶: **H05K 9/00**

(21) Application number: **99303101.2**

(22) Date of filing: **21.04.1999**

(84) Designated Contracting States:
**AT BE CH CY DE DK ES FI FR GB GR IE IT LI LU
MC NL PT SE**
Designated Extension States:
AL LT LV MK RO SI

(72) Inventor: **Terashima, Kiminori**
Soma-shi, Fukushima-ken (JP)

(74) Representative: **Kensett, John Hinton**
Saunders & Dolleymore,
9 Rickmansworth Road
Watford, Hertfordshire WD1 7HE (GB)

(30) Priority: **11.05.1998 JP 12705298**


(71) Applicant: **ALPS ELECTRIC CO., LTD.**
Ota-ku Tokyo 145 (JP)

(54) **Electronic device**

(57) In the electronic device of the present invention, leg portions (1b) of a frame are projected downward from the underside of a printed circuit board (2), so the positioning of the electronic device can be done by inserting the leg portions into holes formed in a mother

printed circuit board. Thus, when the electronic device is surface-mounted to the mother board, there is no fear of its dislocation even under vibration or shock. Accordingly, the electronic device is not deteriorated at all in its quality.

FIG. 1



Description

[0001] The present invention relates to an electronic device suitable for use in, for example, transmitter-receiver unit of a portable telephone.

[0002] A conventional electronic device will now be described with reference to FIGS. 6 to 8. A box-shaped frame 21 formed by a metallic plate is provided with side walls 21a which define an inside space having upper and lower openings and is also provided with mounting legs 21b formed in the side walls 21a.

[0003] On a printed circuit board 22 is formed a conductive pattern 23, to which various electric parts (not shown) are soldered to constitute a desired circuit.

[0004] The printed circuit board 22 is inserted from below the frame 21 into the inside space defined by the frame 21 and is secured to the frame by bending the mounting legs 21b inwards.

[0005] The mounting legs 21b and the conductive pattern 23 are soldered together at 24 to earth the conductive pattern 23 to the frame 21.

[0006] As shown in FIG. 8, the electronic device such as a transmitter-receiver unit constructed as above is then mounted onto such as a mother printed circuit board 25 of the portable telephone and is used.

[0007] In this case, the electronic device is surface-mounted onto the mother printed circuit board 25. More particularly, first the electronic device is put on a predetermined place of the mother printed circuit board 25 and thereafter a cream solder is applied to each corner portion between a conductive pattern 26 on the mother board 25 and the frame 21 of the electronic device.

[0008] Then, the mother board 25 and the electronic device are put on a belt (not shown) and are conveyed to a reflow treatment device to ensure soldering between the conductive pattern 26 on the mother board 25 and the frame 21.

[0009] In the conventional electronic device, the frame 21 is mounted merely by being put on the mother board 25, so at the time of surface mounting there is a fear that soldering may be done in a dislocated state of the electronic device from a predetermined position on the mother board due to vibration or shock. Therefore, the quality of the device may deteriorate.

[0010] Further, since soldering is performed at corner portions between the frame 21 and the mother board 25, there arises the problem that at the time of surface mounting the solder spreads along the corner portions and hence becomes thinner, thus resulting in the soldering being not effected to a satisfactory extent.

[0011] According to the present invention, for solving the above-mentioned problems, there is provided an electronic device comprising a metallic frame having side walls and leg portions projecting downward from the side walls and a printed circuit board having through portions, the through portions being each constituted of a through hole or cutout portion, and wherein the printed circuit board is put on the underside of the frame in a

partially outwardly projected state of the printed circuit board from the side walls, and the leg portions of the frame are inserted into the through portions of the printed circuit board and are projected downward from the underside of the same board.

[0012] Preferably, the leg portions are tightly fitted in the through portions.

[0013] Preferably, the leg portions each have a tapered portion which is wider gradually from its base end portion toward its tip end portion.

[0014] Preferably, the printed circuit board has gap portions contiguous to the through portions.

[0015] Preferably, the gap portions are each adjacent to a side end portion of the printed circuit board and partially opened in the side end portion.

[0016] Preferably, the printed circuit board has a conductive pattern in proximity to the leg portions.

[0017] Embodiments of the invention will now be described, by way of example only, with reference to the accompanying drawings, in which:

FIG. 1 is a partial exploded perspective view of an electronic device according to an embodiment of the present invention;

FIG. 2 is a sectional view of a principal portion of the electronic device;

FIG. 3 is a partially cut-away plan view of the electronic device;

FIG. 4 is a sectional view of a principal portion showing a mounted state of the electronic device;

FIG. 5 is a sectional view of an electronic device according to another embodiment of the present invention;

FIG. 6 is a partial perspective view of a conventional electronic device;

FIG. 7 is a sectional view of a principal portion of the conventional electronic device; and

FIG. 8 is a sectional view of a principal portion showing a mounted state of the conventional electronic device.

[0018] Electronic devices embodying the present invention will be described hereinafter with reference to FIGS. 1 to 5. FIG. 1 is a partial exploded perspective view of an electronic device according to an embodiment of the present invention, FIG. 2 is a sectional view of a principal portion of the electronic device, FIG. 3 is a partially cut-away plan view of the electronic device, FIG. 4 is a sectional view of a principal portion showing an installed state of the electronic device, and FIG. 5 is a sectional view of an electronic device according to another embodiment of the present invention.

[0019] The construction of an electronic device according to an embodiment of the present invention will now be described with reference to FIGS. 1 to 4. A box-shaped frame 1 formed by a metallic plate is provided with side walls 1a which define an inside space having upper and lower openings and is also provided with a

plurality of leg portions 1b projecting downward from the lower ends of the side walls 1a.

[0020] A printed circuit board 2 has through portions 2a each constituted of an arcuate through recess, gap portions 2b contiguous to the through portions 2a respectively and each constituted of an arcuate through recess, and open portions 2d each formed by opening part of the associated gap portion 2b in a side end portion 2c.

[0021] The through portions 2a and the gap portions 2b may each be formed by a hole formed through the printed circuit board 2.

[0022] A conductive pattern 3 is formed on the printed circuit board 2 and various electric parts (not shown) are soldered to the conductive pattern 3 to constitute a desired circuit.

[0023] As shown in FIGS. 2 and 3, the printed circuit board 2 is put on the underside of the frame 1 in a partially outwardly projected state from the side walls 1a.

[0024] In this case, the leg portions 1b of the frame 1 are projected downward from the underside of the printed circuit board 2 while being tightly fitted respectively in the through portions 2a of the printed circuit board 2.

[0025] By such tight fitting of the frame leg portions 1b in the through portions 2a of the printed circuit board 2 the same board is secured to the frame 1. If necessary, the leg portions 1b and the conductive pattern 3 may be soldered together to ensure a firm installation of the printed circuit board and earthing of the conductive pattern 3 to the frame 1.

[0026] The electronic device such as a transmitter-receiver unit thus constructed is mounted onto, for example, a mother printed circuit board 5 of a portable telephone and is used, as shown in FIG. 4.

[0027] In this case, the electronic device is surface-mounted onto the mother board 5. More specifically, first, the electronic device is put on the mother board 5 while inserting the leg portion 1b projecting from the underside of the printed circuit board 2 into holes 5a formed in the mother board to effect positioning of the electronic device with respect to the mother board.

[0028] A cream solder is applied into the gap portions 2b of the printed circuit board 2, allowing the cream solder to be present between a conductive pattern 6 on the mother board 5 and each frame leg portion 1b of the electronic device.

[0029] Next, the mother board 5 and the electronic device are put on a belt (not shown) and are conveyed to a reflow treatment device, in which the conductive pattern on the mother board and the frame 1 are soldered together at 7.

[0030] Referring to FIG. 5, there is illustrated an electronic device according to another embodiment of the present invention. In this embodiment, leg portions 1b of a frame 1 are each formed with a tapered portion 1c which is wider gradually from its base end portion toward its tip end portion.

[0031] The tapered portions 1c function to prevent the

printed circuit board 2 from coming off the frame 1 when the printed circuit board is brought into engagement with the leg portions 1b of the frame.

[0032] Other constructional points are the same as in the previous embodiment, so common components are identified by the same reference numerals and explanations thereof will be omitted.

[0033] According to the electronic device of the present invention, as set forth above, the leg portions 1b of the frame 1 are projected from the underside of the printed circuit board 2. By inserting the leg portions 1b into the holes 5a of the mother printed circuit board 5, it is possible to effect positioning of the electronic device and prevent the electronic device from being dislocated even under vibration or shock at the time of surface-mounting of the electronic device. Consequently, the electronic device is free of any defect in its quality.

[0034] Besides, the frame 1 and the printed circuit board 2 can be combined together by tightly fitting the leg portions 1b into the through portions 2a of the printed circuit board 2. It is not necessary to perform such an operation as caulking. Thus, it is possible to provide an electronic device superior in productivity.

[0035] Moreover, where the leg portions 1b are each formed with the tapered portion 1c which is wider gradually from its base end portion toward its tip end portion, it is possible to surely prevent the printed circuit board 2 from coming off the leg portions 1b, and the printed circuit board 2 can be surely brought into abutment against the underside of the side walls 1a of the frame 1. Thus, it is possible to provide an electronic device of a high accuracy.

[0036] Further, by forming the gap portions 2b contiguous to the through portions 2a in the printed circuit board 2, it is possible to let the gap portions 2b serve as solder sumps. Thus, it is possible to provide an electronic device capable of being soldered firmly onto the mother board 5.

[0037] Further, by forming the open portion 2d in each gap portion 2b it is possible to enlarge the gap portion 2b, so that the application of a cream solder becomes easier and it is possible to effect soldering over a wider area. Thus, it is possible to provide an electronic device which can be soldered reliably.

[0038] Further, by forming the conductive pattern 3 in proximity to the leg portions 1b on the printed circuit board 2, it is possible to effect soldering of the printed circuit board with the conductive pattern simultaneously with soldering of the conductive pattern 6 on the mother board 5 with the leg portions 1b. Therefore, it is possible to save the trouble of soldering the conductive pattern 3 to the frame 1 and hence possible to provide an electronic device superior in productivity.

Claims

1. An electronic device comprising:

a metallic frame having side walls and leg portions projecting downward from said side walls; and

a printed circuit board having through portions, said through portions being each constituted of a through hole or cutout portion, and wherein said printed circuit board is put on the underside of said frame in a partially outwardly projected state of the printed circuit board from said side walls, and said leg portions of said frame are inserted into said through portions of the printed circuit board and are projected downward from the underside of the printed circuit board.

5

10

15

2. An electronic device according to claim 1, wherein said leg portions are tightly fitted in said through portions.
3. An electronic device according to claim 2, wherein said leg portions each have a tapered portion which is wider gradually from its base end portion toward its tip end portion.
4. An electronic device according to any of claims 1 to 3, wherein said printed circuit board has gap portions contiguous respectively to said through portions.
5. An electronic device according to claim 4, wherein said gap portions are each adjacent to a side end portion of said printed circuit board and partially opened in said side end portion.
6. An electronic device according to any preceding claim, wherein said printed circuit board has a conductive pattern in proximity to said leg portions.

20

25

30

35

40

45

50

55

FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6
PRIOR ART




FIG. 7
PRIOR ART






FIG. 8
PRIOR ART





(19)

Europäisches Patentamt
European Patent Office
Office européen des brevets



(11)

EP 0 957 665 A3

(12)

EUROPEAN PATENT APPLICATION

(88) Date of publication A3:
19.04.2000 Bulletin 2000/16

(51) Int Cl.7: **H05K 9/00**

(43) Date of publication A2:
17.11.1999 Bulletin 1999/46

(21) Application number: **99303101.2**

(22) Date of filing: **21.04.1999**

(84) Designated Contracting States:
**AT BE CH CY DE DK ES FI FR GB GR IE IT LI LU
MC NL PT SE**
Designated Extension States:
AL LT LV MK RO SI

(72) Inventor: **Terashima, Kiminori**
Soma-shi, Fukushima-ken (JP)

(74) Representative: **Kensett, John Hinton**
Saunders & Dolleymore,
9 Rickmansworth Road
Watford, Hertfordshire WD1 7HE (GB)

(30) Priority: **11.05.1998 JP 12705298**


(71) Applicant: **ALPS ELECTRIC CO., LTD.**
Ota-ku Tokyo 145 (JP)

(54) Electronic device

(57) In the electronic device of the present invention, leg portions (1b) of a frame are projected downward from the underside of a printed circuit board (2), so the positioning of the electronic device can be done by inserting the leg portions into holes formed in a mother

printed circuit board. Thus, when the electronic device is surface-mounted to the mother board, there is no fear of its dislocation even under vibration or shock. Accordingly, the electronic device is not deteriorated at all in its quality.

FIG. 1





European Patent
Office

EUROPEAN SEARCH REPORT

Application Number
EP 99 30 3101

DOCUMENTS CONSIDERED TO BE RELEVANT					
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (Int.Cls)		
X	DE 81 23 367 U (STANDARD ELEKTRIK) 24 December 1981 (1981-12-24) * the whole document *	1,2,4,6	H05K9/00		
X	EP 0 265 285 A (INSTR SPECIALTIES CO INC) 27 April 1988 (1988-04-27) * the whole document *	1			
X	DE 39 22 461 A (ALPS ELECTRIC CO LTD) 11 January 1990 (1990-01-11) * figure 2 *	1,4,5			
A	WO 94 06268 A (THOMSON CONSUMER ELECTRONICS ;ELLIOTT CHARLES ANTHONY (US)) 17 March 1994 (1994-03-17) * the whole document *	1			
A	DE 295 05 327 U (SIEMENS AG) 3 August 1995 (1995-08-03)	1-3			
A	US 4 861 941 A (KUBO KAZUHIKO ET AL) 29 August 1989 (1989-08-29)	1,2	<table border="1"> <tr> <td>TECHNICAL FIELDS SEARCHED (Int.Cls)</td> </tr> <tr> <td>H05K</td> </tr> </table>	TECHNICAL FIELDS SEARCHED (Int.Cls)	H05K
TECHNICAL FIELDS SEARCHED (Int.Cls)					
H05K					
The present search report has been drawn up for all claims					
Place of search THE HAGUE		Date of completion of the search 25 February 2000	Examiner Toussaint, F		
CATEGORY OF CITED DOCUMENTS X: particularly relevant if taken alone Y: particularly relevant if combined with another document of the same category A: technological background O: non-written disclosure P: intermediate document		T: theory or principle underlying the invention E: earlier patent document, but published on, or after the filing date D: document cited in the application L: document cited for other reasons &: member of the same patent family, corresponding document			

EPO FORM 1600 (03/02) (P04001)

**ANNEX TO THE EUROPEAN SEARCH REPORT
ON EUROPEAN PATENT APPLICATION NO.**

EP 99 30 3101

This annex lists the patent family members relating to the patent documents cited in the above-mentioned European search report. The members are as contained in the European Patent Office EDP file on
The European Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

25-02-2000

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
DE 8123367	U	24-12-1981	NONE	
EP 0265285	A	27-04-1988	US 4754101 A JP 1086594 A	28-06-1988 31-03-1989
DE 3922461	A	11-01-1990	US 4948923 A	14-08-1990
WO 9406268	A	17-03-1994	CN 1083655 A DE 69300740 D DE 69300740 T EP 0610476 A ES 2082657 T JP 7500952 T MX 9305191 A US 5644101 A	09-03-1994 07-12-1995 20-06-1996 17-08-1994 16-03-1996 26-01-1995 31-05-1994 01-07-1997
DE 29505327	U	03-08-1995	EP 0735811 A	02-10-1996
US 4861941	A	29-08-1989	JP 1943043 C JP 6069120 B JP 63001099 A DE 3790315 C DE 3790315 T GB 2200253 A,B WO 8707998 A	23-06-1995 31-08-1994 06-01-1988 23-11-1989 04-08-1988 27-07-1988 30-12-1987

EPO FORM P449

For more details about this annex : see Official Journal of the European Patent Office, No. 12/82

THIS PAGE BLANK (USPTO)